









AXON EASY 400

DC charging station that provides ultra-fast and friendly high-power charging. It is available in multiple power and connector configurations. The charger's new ease-of-use features respond to drivers' growing need for convenient, fast charging and intuitive operation. The device is adaptable to different weather conditions and is easy to install and use. The charger's modern design complements the urban architecture of today's city centers. This versatile and innovative device is suitable for integration with all charging service providers.

-  Highways
-  Parkings
-  Charging stations
-  City centers
-  Service areas
-  Commercial areas



Power	240, 320, 400 kW
Device type	All-In-One Charging Station
Power Split	Dynamic Load Balancing System (DLBS)
Power upgrade	240 > 400 320 > 400
Connectors	240, 320, 400 kW CCS / CCS, CCS HPC / CCS HPC
Voltage range	150 - 1000 V
Max. charging current	CCS - 400 A (up to 500 A) CCS HPC - 500 A
Selection of options	Connectors & cables lenght Meters AD Display Branding Power split Payment terminals Reactive power compensation
Metering standard	Eichrecht, MID compliant
Plug & Charge	ready

POWER THAT
MOVES YOU

ekoenergetyka.com

Find out more



PHOTOMATE
OFFICIAL DISTRIBUTOR

photomate.eu



Cable Management System (CMS) with flat arm and braking mechanism

LED lighting to indicate the occupied status of the charging point (wide visibility)

Panel illumination and functional lightning integrated, indicating charging level status (SOC)

High efficiency of ventilation system while maintaining low noise emissions < 60 dBA

Weatherproof and vandal resistant housing -35°C +55°C

Advertising screen (24") for independent management of advertising content

Operation via intuitive 10" screen integrated with RFID

Comfortable screen visibility with day/night mode

Different variants of terminals and payment operators

Four-side service access

+ Remote diagnostics and software updates

+ Comfort of use for people with limited mobility

DYNAMIC LOAD BALANCING SYSTEM

Axon Easy 400 kW	
0 kW / 400 kW	280 kW / 120 kW
40 kW / 360 kW	360 kW / 40 kW
120 kW / 280 kW	400 kW / 0 kW
200 kW / 200 kW	

SELECT OPTIONS TO DESIGN YOUR PERFECT AXON EASY



Branding (Mini, Midi, Maxi)



Connector extension (DC uncooled up to 7 or 9 m)



Payment terminals and operators (PAX IM30 - CCV / eService, Payter Apollo - Cloud Solutions, Valina -Worldline)



Meters (Eichrecht, MID)



AD Display (individual or public advertising use)



Power upgrade (240 > 400kW, 320 > 400 kW)



Reactive power compensation (Active reactive power compensation)

